



NOTES:

1. INLET TUBING MUST BE FLARED, IF COPPER.
2. RESIDENTIAL PRV's, IF NEEDED, SHOULD BE LOCATED BETWEEN THE INLET VALVE AND METER HORN.
3. 1" METERS OR SMALLER SHALL USE A COPPER HORN.
4. IF THE METER IS BOXED OR PLACED BEHIND A WALL, PROVIDE AN ACCESS OPENING 36" WIDE FROM ABOVE THE OUTLET VALVE TO THE FLOOR.
5. VALVES MUST BE ACCESSIBLE FROM THE OPENING.
6. METER MUST BE CENTERED IN ANY OPENING.
7. GOLDEN VALLEY ONLY MAINTAINS THE METER AND REMOTE READING DEVICE.
8. METER SHALL BE PROTECTED FROM FREEZING.
9. BALL VALVES SHALL BE INSTALLED APPROXIMATELY 12" ON EITHER SIDE OF THE METER.
10. CUSTOMER MUST CALL GOLDEN VALLEY UTILITY INSPECTIONS FOR WIRING AND INSPECTION OF THE METER PRIOR TO FINISHING INTERIOR WALLS OF THE BUILDING.

NOT TO SCALE

APPROVED JANUARY 1, 2024

CITY ENGINEER REG 23110

**RESIDENTIAL
WATER METER
INSTALLATION**

City of
Golden Valley
GV-WM-110